

## Cisco Model DPC3216 DOCSIS 3.0 16x4 Cable Modem with Embedded Digital Voice Adapter

Get a faster connection to the Internet with a cable modem designed with 16 bonded downstream channels that deliver over 500 Mbps and four bonded upstream channels that deliver over 120 Mbps. That's up to 16 times faster than conventional single-channel DOCSIS<sup>®</sup> 2.0 cable modems. And it's all available with the Cisco<sup>®</sup> Model DPC3216 DOCSIS 3.0 16x4 Cable Modem (DPC3216) with embedded digital voice adapter.

The Cisco DPC3216 (Figure 1) uses advanced line interface technology to provide multi-country, toll-quality telephone service using existing in-home wiring. The Cisco DPC3216 features single-line or two RJ-11 telephone ports for voice, and it supports a total of 10 ringer equivalence number (REN) loading, 5 REN per phone line.

**Figure 1.** Cisco DPC3216 DOCSIS 3.0 16x4 Cable Modem with Embedded Digital Voice Adapter (Image May Vary from Actual Product and Specification)



The Cisco DPC3216 is designed to meet PacketCable<sup>™</sup> 1.5 and DOCSIS 3.0 specifications and is backward compatible with DOCSIS 2.0, 1.1, and 1.0 networks. It fully supports the CODECs specified in PacketCable 1.5. Additional CODECs are available through a software upgrade that includes a high-fidelity CODEC option for toll-quality-plus service. Standard VoIP call signaling is compliant with PacketCable Media Gateway Control Protocol/Network-based Call Signaling (MGCP/NCS) specifications. Software upgrades are available to support Session Initiation Protocol (SIP) call signaling.

## Features

### DOCSIS

- Sixteen (16) bonded downstream channels with data rates that can be faster than 500 Mbps
- Four (4) bonded upstream channels with data rates that can be faster than 120 Mbps
- Designed to meet DOCSIS 3.0 specifications as well as backward compatibility with existing DOCSIS 2.0, 1.1, and 1.0 networks
- DOCSIS-compliant support for IPv6/IPv4
- Expanded tuning range, 88-1002 MHz
- Some hardware configurations provide battery powered backup on loss of AC power

### Embedded Digital Voice Adapter

- Two-line embedded digital voice adapter for wired telephony service
- Toll-quality, high-compression, and high-fidelity (exceeding toll quality) CODEC options

### Connections

- One 10/100/1000BASE-T Ethernet ports to provide wired connectivity
- High-performance broadband Internet connectivity to energize your online experience

### Design and Function

- Attractive compact design and versatile orientation to stand vertically, lie flat on the desktop or shelf, or mount easily on a wall
- Dual-color LED status indicators on the front panel indicate cable modem operational status
- TR-068-compliant color-coded connectors and cables simplify installation and setup

### Management

- Software upgradeable by network download
- Remote manageability using SNMP V1/V2 and V3

### Software and Documentation

- User guide can be downloaded from Cisco.com

**Figure 2.** Cisco DPC3216 Front Panel (Image May Vary from Actual Product and Specification)



**Table 1.** Front Panel Features

Feature	Description
Indicators	POWER, DS, US, ONLINE, LINK, TEL1, TEL2, and BATTERY (on select models)
Color	Black, black lens, silver text
Branding	Cisco logo and model number

**Figure 3.** Cisco DPC3216 Back Panel (Image May Vary from Actual Product and Specification)



**Table 2.** Back Panel Switch and Connections

Feature	Description
<b>Power connector</b> Color: black	Connects modem to the AC power via the power cord (supplied)
<b>Telephone 1 and 2</b> Color: gray	One RJ-14 and one RJ-11 telephone jack connect to home telephone wiring and to conventional telephones or fax machines
<b>ETHERNET</b> Connector Color: Yellow	RJ-45 Ethernet port connects to the Ethernet port on your PC or your home network
<b>Reset</b>	Recessed button on the back panel which performs a reset of the EPC3940
<b>Cable connector</b>	F-connector connects to an active cable signal from your service provider

## Product Specifications

**Table 3.** Product Specifications

Specification	Value
<b>Voice Specifications</b>	
<b>Call Signaling Protocol</b>	<ul style="list-style-type: none"><li>• MGCP/NCS including configurable IPsec encryption</li><li>• Configurable to support RFC2833 event signaling</li><li>• Supports Bell103 protocol</li><li>• Software upgradeable to support Session Initiation Protocol (SIP)</li><li>• The following SIP standards are supported:<ul style="list-style-type: none"><li>◦ RFC 2617 HTTP Authentication: Basic and Digest Access Authentication</li><li>◦ RFC 2976 The SIP INFO Method</li><li>◦ RFC 3261 SIP: Session Initiation Protocol</li><li>◦ RFC 3262 Reliability of Provisional Responses in Session Initiation Protocol (SIP)</li><li>◦ RFC 3263 Session Initiation Protocol (SIP): Locating SIP Servers</li><li>◦ RFC 3264 An Offer/Answer Model with Session Description Protocol (SDP)</li><li>◦ RFC 3265 Session Initiation Protocol (SIP)-Specific Event Notification</li></ul></li></ul>

Specification	Value
	<ul style="list-style-type: none"> <li>◦ RFC 3420 Internet Media Type message/sipfrag</li> <li>◦ RFC 3428 Session Initiation Protocol (SIP) Extension for Instant Messaging</li> <li>◦ RFC 3515 The Session Initiation Protocol (SIP) Refer Method</li> <li>◦ RFC 3842 A Message Summary and Message Waiting Indication Event Package for the Session Initiation Protocol (SIP)</li> <li>◦ RFC 3892 The Session Initiation Protocol (SIP) Referred-By Mechanism</li> <li>◦ RFC 3903 Session Initiation Protocol (SIP) Extension for Event State Publication</li> <li>◦ Draft-ietf-mmusic-sdp-new-24 SDP: Session Description Protocol (Replacement for RFC 2327)</li> <li>◦ Draft-ietf-sipping-cc-transfer-01 Session Initiation Protocol Call Control – Transfer</li> <li>◦ Draft-ietf-sip-session-timer-08 The SIP Session Timer</li> <li>◦ Draft-ietf-sipping-realtimefax-01 SIP Support for Real-time Fax: Call Flow Examples and Best Current Practices</li> <li>◦ Draft-ietf-mmusic-sdescription-09 Session Description Protocol Security</li> <li>◦ Descriptions for Media Streams</li> <li>◦ Draft-ietf-sip-replaces-02 The Session Initiation Protocol (SIP) "Replaces" Header Provisioning Modes</li> </ul>
<b>Provisioning Modes</b>	<ul style="list-style-type: none"> <li>• Full PacketCable secure provisioning mode</li> <li>• Kerberos support with NVRAM ticket caching</li> <li>• Configurable PacketCable-lite (MTA config file provisioning without security)</li> <li>• Configurable for non-PacketCable (MTA configuration using DOCSIS config file) CODECs</li> </ul>
<b>CODECs</b>	<p>Standard: G.711, T.38 Fax Relay, iLBC and BV16</p> <p>Software upgradeable to support other CODEC combinations, including:</p> <ul style="list-style-type: none"> <li>• G.711 and G.728</li> <li>• G.711 and G.729</li> <li>• G.711 and G.729 a/e</li> <li>• G.711 and BV16 and BV32 (High fidelity – near CD quality)</li> <li>• G.711 and G.723</li> <li>• G.711 and G.726</li> </ul> <p><b>Note:</b> Other codec combinations can be downloaded as required.</p>
<b>CODEC Packetization Intervals</b>	10, 20, and 30 ms
<b>CODEC Synchronization</b>	CODEC synchronization to UGS time clock allows slip-free end-to-end sync to PSTN clock (reduces frame slips that can cause Fax/Analog Modem call failures)
<b>CODEC Encryption</b>	Configurable to support AES-128 encryption or no encryption modes
<b>Hearing Impaired Services Support</b>	TDD support including detection of V.18 including Annex A
<b>Fax and Analog Modem Support</b>	DSP-based Modem/Fax Tone detection and support for Voice Band Data Mode with auto-CODEC negotiation and auto-control of echo canceller, jitter buffer, and Voice Activation Detection (VAD)
<b>Jitter Buffer Support</b>	Adaptive dynamically controlled
<b>Latency Control</b>	Configurable min/ max jitter buffer size
<b>Audio Gain Levels</b>	Independently configurable Tx and Rx audio gains
<b>Silence Suppression</b>	Configurable VAD with comfort noise generation
<b>Packet Loss Concealment</b>	ANSI T1.521-1999
<b>Call Connection Quality Monitoring</b>	RTCP, RFC1889, RFC1890, SNMP MIB for last call quality statistics
<b>Dialing Modes</b>	DTMF and configurable pulse dial support
<b>DTMF Relay</b>	RFC2833 including fast (40ms) DTMF Relay for alarm system signaling compatibility
<b>Layer 2 Quality of Service</b>	<ul style="list-style-type: none"> <li>• Full PacketCable highly secure DQOS with GateID including UGS and UGS/AD</li> <li>• DQOS Lite support including UGS and UGS/AD</li> </ul>
<b>Layer 3 Quality of Service</b>	Configurable DiffServe/TOS support for Signaling, RTP, and RTCP flows
<b>Payload Header Suppression (PHS)</b>	<ul style="list-style-type: none"> <li>• Supported for RTP and RTCP packet flows to reduce per-call network bandwidth</li> <li>• Advanced support for Dynamic Payload Header Suppression using Propane Technology</li> </ul>
<b>Management</b>	SNMPv3, SNMPv2, and SNMPv1, Telnet/SSH with configurable user ID and password, internal log, and external Syslog support

Specification	Value
<b>Echo Cancellation</b>	G.168 with extended echo tail support
<b>Call Feature Support</b>	<ul style="list-style-type: none"> <li>• Caller ID</li> <li>• Call Waiting with Caller ID</li> <li>• Cancel Call Waiting</li> <li>• Call Conferencing (3-way calls)</li> <li>• Configurable hook flash support</li> <li>• Distinctive Ringing (Configurable for up to 11 ring patterns per phone line)</li> <li>• Ring Splash</li> <li>• Stutter Dial Tone</li> <li>• Off hook warning tone</li> <li>• Open Switch Interval support to enhance answering machine compatibility</li> <li>• Configurable star codes</li> <li>• Euro/US hook-flash type</li> <li>• Call transfer</li> <li>• Message Waiting Indicator</li> <li>• Warm Line</li> <li>• Call Forwarding Unconditional</li> <li>• Call Forwarding on Busy</li> <li>• Call Forwarding No Answer</li> <li>• Call return</li> <li>• Redial Call</li> <li>• Automatic redial</li> <li>• Other call features available with compliant CMS or gateway</li> </ul>
<b>Telephone Ring Loading</b>	Full 5 REN support on each phone line (10 REN total)
<b>Ring Signal</b>	Configurable balanced ring with configurable DC offset
<b>Max Phone Line Distance</b>	Supports up to 1000 ft of 26 AWG (0.4mm) wire on each phone line. Supports operation with typical in-home telephone wiring
<b>Country-Specific Telephone Parameters Supported</b>	United States, Japan, United Kingdom, Germany, France, Belgium, Netherlands, Finland, Italy, Switzerland, Sweden, Denmark, Brazil, Australia, Poland, Czech Republic, Hungary, Romania, ETSI 101 909-18
<b>RF Downstream</b>	
<b>Operating frequency range</b>	108 to 1002 MHz
<b>Tuner frequency range</b>	88 to 1002 MHz
<b>Tuner</b>	1 GHz full-band capture tuner that eliminates restrictions on downstream channel frequency plan
<b>Demodulation</b>	16 demodulators, each demodulator: 64 QAM or 256 QAM
<b>Maximum data rate</b>	16 downstream channels, each 8 MHz channel: 42.88 Mbps for 256 QAM and 30.34 Mbps for 64 QAM
<b>Bandwidth</b>	6 MHz
<b>Operating level range</b>	-15 to +15 dBmV
<b>Input impedance</b>	75 ohms
<b>RF Upstream</b>	
<b>Operating Frequency Range</b>	5 to 42 MHz
<b>Transmitter Frequency Range</b>	5 to 42 MHz
<b>Upstream Transmission</b>	4 upstream channels
<b>Modulation</b>	QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM at ATDMA mode QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM, 128 QAM at SCDMA mode

Specification	Value			
<b>Maximum Data Rate per Channel</b>	<b>Modulation</b>	<b>Channel Bandwidth (MHz)</b>	<b>Raw Data Rate (Mb/s)</b>	
	QPSK	1.6	2.56	
	16 QAM	1.6	5.12	
	QPSK	3.2	5.12	
	16 QAM	3.2	10.24	
	32 QAM	3.2	12.8	
	64 QAM	3.2	15.4	
	16 QAM	6.4	20.5	
	32 QAM	6.4	25.6	
	64 QAM	6.4	30.72	
<b>Bandwidth</b>	200 kHz to 6.4 MHz			
<b>Maximum Operating Level (± 2dB)</b>	<b>Modulation</b>	<b>1 Channel</b>	<b>2 Channels</b>	<b>3 or 4 Channels</b>
<b>TDMA</b>	QPSK	+61 dBmV	+58 dBmV	+55 dBmV
	8 QAM	+58 dBmV	+55 dBmV	+52 dBmV
	16 QAM	+58 dBmV	+55 dBmV	+52 dBmV
	32 QAM	+57 dBmV	+54 dBmV	+51 dBmV
	64 QAM	+57 dBmV	+54 dBmV	+51 dBmV
	<b>SCDMA</b>	QPSK	+56 dBmV	+53 dBmV
	8 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	16 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	32 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	64 QAM	+56 dBmV	+53 dBmV	+53 dBmV
	128 QAM	+56 dBmV	+53 dBmV	+53 dBmV
<b>Electrical</b>				
<b>Input Voltage</b>	12VDC (external power supply)			
<b>Power Consumption (Modem Module)</b>	~ 6.7 watts			
<b>Data Ports</b>	Ethernet 10/100/1000BASE-T (Auto-sensing with Auto-MDIX); RJ-45 Ethernet (1)			
<b>RF</b>	Female "F" type			
<b>Impedance</b>	75 ohms			
<b>Mechanical</b>				
<b>Dimensions (W x D x H) (Approximate; not including "F" connector)</b>	Non-Battery Enclosure: 181mm x 120mm x 64mm Battery Enclosure: 154mm x 139mm x 86mm			
<b>Weight (Approximate; not including battery cartridge)</b>	285g (Non-Battery Enclosure) 419g (Battery Enclosure)			
<b>Battery Type and Capacity</b>	1 cartridge, Li-Ion, 2-Cell 3000mAh			
<b>Operating Temperature</b>	0 to 40° C (32 to 104° F)			
<b>Operating Humidity</b>	0 to 95% RH non-condensing			
<b>Storage Temperature</b>	-20 to 70° C (-4 to 158° F)			
<b>Standards and Approvals</b>				
<b>Designed to Comply with the Following Standards</b>	PacketCable 1.5, 1.0 DOCSIS 3.0, 2.0, 1.1, 1.0			
<b>Regulatory and Safety Approvals</b>	As required per country where the DPC3216 will be used			

## Ordering Information

**Table 4.** Ordering Information

Description	Part Number
<b>Enclosure with One (1) Battery Bay 5-42/54-1002 MHz Diplex Filter</b>	
<b>DPC3216C DOCSIS 3.0 Cable Modem with Embedded Digital Voice Adapter Includes:</b> <ul style="list-style-type: none"><li>• 100-240 VAC/50-60 Hz, External power Supply</li><li>• One (1) 3000mAh Li-Ion Battery provided</li><li>• Ethernet Cable</li><li>• Installation Sheet</li><li>• Safety Sheet</li></ul>	DPC3216C-VCM-K9
<b>Enclosure with No Battery Bay 5-42/54-1002 MHz Diplex Filter</b>	
<b>DPC3216 DOCSIS 3.0 Cable Modem with Embedded Digital Voice Adapter Includes:</b> <ul style="list-style-type: none"><li>• 100-240 VAC/50-60 Hz, External power Supply</li><li>• Ethernet Cable</li><li>• Installation Sheet</li><li>• Safety Sheet</li></ul>	DPC3216-VCM-K9

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)