

## DCM475

DOCSIS 3.0  
Cable Modem



*On January 27<sup>th</sup> 2010, Thomson changed its company name to Technicolor. All product data sheets, including those for products which still carry the Thomson name, now reflect our new Technicolor brand.*

### CABLE

DATA

With the evolution of cable standards, DOCSIS 3.0 will prove decisive for cable operators wishing to provide high bandwidth data delivery and to stay ahead of the content with game and video over IP delivery. With this new generation of High Speed Data Services Solution, Technicolor introduces up to eight (8) bonded downstream channels and four (4) bonded upstream channels, with a design backward-compatible for use as a single-channel with older networks without any service interruption. Thanks to the integrated dual split tuner solution, the operator will benefit from flexibility in channel allocation: to ease the management when the channel frequency plan is loaded or to separate data from other services such as video over IP.

The new DCM475 comes in the sleek attractive design Technicolor has adopted as the new «family look».

## Easy to Use, Easy to Install

As all Technicolor gateways, the GEthernet port DCM475 is an easy to use, easy to install gateway.

For convenience of the end user, the easy-to-access LEDs provide a clear indication of start-up sequence and connectivity status.

Multiple integrated Web pages allow direct access to the status and settings, including privacy and security information.

## Ecological Design

Technicolor, as front-runner in ecological design, offers in the DCM475 advanced features to reduce power consumption. It is designed with advanced power management to better control power consumption, thanks to the integrated tuner. The Gateway even supports a lower power mode thanks to a split tuner solution, an integrated upstream power amp and the auto power down feature on the external GEthernet interfaces. Additional power control features are supported with the ability to turn off any or all modules, to slow down or turn off processors and to turn off all external interfaces, reducing the power consumption even more.

## Features at a Glance

- DOCSIS 3.0 certified
- 64 MHz dual tuner fully compliant with DOCSIS 3.0
- 1 Gigabit Ethernet port
- MPEG2 over IP Encapsulation solution
- Reliable high-performance platform
- Powerful processor and architecture
- Advanced Power Control
- BPI+ communications privacy to support secure data exchange between modems & cable operator's servers



# DCM475

DOCSIS 3.0

Cable Modem

## Advanced Diagnostics

- Advanced web pages to facilitate installation and troubleshooting
- Easy configuration and set-up
- Remote access via SNMP, Web Page
- Post-installation easily managed with SNMP

# DCM475

DOCSIS 3.0  
Cable Modem



## Technical Specifications

### Standards / Certifications

- Data DOCSIS 3.0 certified
- CMTS Interoperability Any qualified DOCSIS CMTS

### Receiver

- Downstream Modulation QAM 64/256
- Downstream Frequency Range 54-1002 MHz
- Maximum Downstream Data Range 340 Mbps (theoretical) (42.88 Mbps x 8 channels)
- Capture Windows 64 MHz capture window split into two windows of 32 MHz thanks to the integrated dual tuner solution
- Number of Downstreams up to 8
- Input Signal Level Range -15dBmV ~ + 15dBmV
- Input Impedance 75 Ohm

### Transmitter

- Upstream Modulation QPSK and 8, 16, 32, 64 and 128 QAM
- Number of Uptreams 4
- Upstream Frequency Range 5-42 MHz
- Maximum Upstream Data Range 131 Mbps (theoretical) (32.78 Mbps x 4 channels)
- Channel Bandwidth 200, 400 and 800kHz, 1.6, 3.2 and 6.4 MHz
- Output Impedance 75 Ohm

### PC Compatible

- Operating Systems Windows 2000, XP and Vista
- Ethernet Port 10/100/1000 Base-T
- Drive CD-ROM

### Software Features

- Software Downloadable yes
- Multiple Client Support 32
- Class of Services (CoS) 16 SIDs
- Protocol Filtering Ethernet & IP
- SNMP Management V2, V3
- Security BPI+
- HTTP Server (CM status) yes
- Local configuration yes
- Through HTTP server yes

### Interfaces / Physical

- Giga Ethernet 1 x RJ45 10/100/1000 Base-T auto detect
- RF Connector 1 x F-Type
- Button Reset
- LEDs Power, DS, US, Online, Link
- Power Supply External, 120VAC 60Hz
- Operating Temperature 32° F to 104° F
- Operating Humidity 20% to 90% non-condensing
- Storage Temperature -4° F to 158° F
- Safety FCC Part 15

### Packaging Information

- Cabinet Dimensions in: 5.9 (L) x 5.9 (D) x 1.18 (H)
- Cabinet Weight Approx. 0.306 lb
- Packaging Dimensions in: 9.05 (L) x 8.58 (D) x 2.87 (H)
- Shipping Weight Approx. 1.356 lb
- Master-pack Dimensions mm: 18.74 (L) x 15.23 (D) x 7.87 (H)
- Master-pack Shipping Weight Approx. 15.65 lb
- Master-pack Quantity 10 units

### Content of the Box

- Cable Modem
- Power supply
- Ethernet Cable
- CD-ROM

Technicolor Professional Services are available to address your demands for qualified technical support & warranty, product maintenance, access to training courses and tailor-made solutions to specific product evolution. For more information, please ask your usual contact person.

TECHNICOLOR WORLDWIDE HEADQUARTERS  
1, rue Jeanne d'Arc  
92443 Issy-les-Moulineaux France  
Tel. : 33(0)1 41 86 50 00 - Fax : 33 (0) 1 41 86 58 59

[www.technicolor.com](http://www.technicolor.com)

SALES CONTACT  
For more information please get in touch with your usual sales representative or use the following email:

[cablesales@technicolor.com](mailto:cablesales@technicolor.com)



© Copyright 2010 Technicolor. All rights reserved. Photos and specifications subject to change without notice. All trade names referenced are service marks, trademarks, or registered trademarks of their respective companies. DS-004-v03-0111